



803

GOLFARE MASCHIO 8.8
EYE BOLT 8.8
 ANNEAU DE LEVAGE MALE 8.8
 RINGSCHRAUBEN 8.8




Coefficiente di sicurezza: 4
Safety ratio: 4
 Coefficient de sécurité: 4
 Sicherheitsfaktor: 4

Avvitare a mano
To be screwed by hand
 A visser a main
 Von Hand aufschrauben

Codice Code Code	Misura Size Measure Abmessung	A	B	C	E	F	H	Peso Weight Poids Gewicht
	D x L (mm)	mm	mm	mm	mm	mm	mm	Kg
C80306	M6x13	25	45	25	10	10	45	0,090
C80308	M8x13	25	45	25	10	10	45	0,090
C80310	M10x17	25	45	25	10	10	45	0,110
C80312	M12x21	35	63	35	14	14	62	0,270
C80314	M14x21	35	63	35	14	14	62	0,290
C80316	M16x27	35	63	35	14	14	62	0,310
C80318	M18x27	50	90	50	20	20	90	0,840
C80320	M20x30	50	90	50	20	20	90	0,860
C80322	M22x36	50	90	50	20	20	90	0,900
C80324	M24x36	50	90	50	20	20	90	0,900
C80327	M27x45	60	108	65	24	24	109	1,660
C80330	M30x45	60	108	65	24	24	109	1,700
C80333	M33x54	70	126	75	26	28	128	2,000
C80336	M36x54	70	126	75	26	28	128	2,150
C80342	M42x63	80	144	85	30	32	147	4,150
C80348	M48x68	90	166	100	35	38	168	6,200
C80356	M56x78	100	184	110	38	42	187	8,800
C80364	M64x90	110	206	120	42	48	208	12,400

WORKING LOAD LIMIT W.L.L (t)



Codice Code Code	Misura Size Measure Abmessung	0°	0°	0°-45°	45°-60°	0°-45°	45°-60°	Coppia max di serraggio Max tightening couple Max couple de serrage Max Drehmoment
		1 braccio Single leg 1 brin 1 Strang	2 bracci 2 legs 2 brins 2 Stränge	2 bracci 2 legs 2 brins 2 Stränge	2 bracci 2 legs 2 brins 2 Stränge	3/4 bracci 3/4 legs 3/4 brins 3/4 Stränge		(Nm)
C80306	M6x13	0,4	0,8	0,14	0,1	0,2	0,14	3,5
C80308	M8x13	0,8	1,6	0,28	0,2	0,4	0,28	8
C80310	M10x17	1	2	0,35	0,25	0,5	0,35	16
C80312	M12x21	1,6	3,2	0,56	0,4	0,8	0,56	28
C80314	M14x21	3	6	1	0,75	1,5	1	45
C80316	M16x27	4	8	1,4	1	2	1,4	70
C80318	M18x27	5	10	1,8	1,25	2,5	1,8	95
C80320	M20x30	6	12	2,1	1,5	3	2,1	135
C80322	M22x36	7	14	2,4	1,75	3,5	2,4	182
C80324	M24x36	8	16	2,8	2	4	2,8	230
C80327	M27x45	10	20	3,5	2,5	5	3,5	343
C80330	M30x45	12	24	4,2	3	6	4,2	465
C80333	M33x54	14	28	4,8	3,4	6,8	4,8	632
C80336	M36x54	16	32	5,6	3,9	7,8	5,4	814
C80342	M42x63	24	48	8,4	5,9	11,8	8,2	1304
C80348	M48x68	32	64	11,2	7,8	15,6	10,9	1981
C80356	M56x78	36	72	12,6	8,8	17,6	12,3	3000
C80364	M64x90	45	90	15,7	11	22	15,4	4736

EYE NUT 8.8

ANNEAU DE LEVAGE FEMELLE 8.8
 RINGMUTTER 8.8



EYE BOLT WITH SCREW 8.8

ANNEAU DE LEVAGE ORIENTABLE AVEC VIS 8.8
 RINGSCHRAUBEN VARIABEL 8.8

